



### FEATURES:

- High quality Video Performance
- High quality Construction
- UL listed power supply
  - 5 Year Warranty
  - Made in USA

The **CS-14** switcher is an RS-232 controlled, 4 video input with 2 video output vertical interval switcher. Front panel controls are for local monitoring on video out #1 while video out #2 is fed to the remote computer access system.

## SPECIFICATIONS

Video:		Operational:	
Inputs (4):	Composite Video	Baud Rate:	9600 Baud, Preset
Input Connectors:	BNC	RS-232 Connections (2):	2.5mm RCA Jack
Input Level:	1.0VPP Nominal, 2VPP Max	Control Commands:	Predefined ASCII Codes For
Input Impedance:	75ohm +/-5%		Unit ID And Input Select
Outputs (1):	Composite Video	Power Requirements:	
Output Connectors:	BNC	Power Connector:	3.5mm Phono Plug, Center +
Output Impedance:	75ohm +/-5%	AC Operation:	Use 12VDC AC Adapter
Gain In/Out:	Unity Into 75ohms +/- 10%	DC Power Input:	12 To 20VDC Ungrounded
Frequency Response:	0-5MHz +/- .5dB	DC Power Draw:	<2.5 VA
	5-15MHz + 1.0dB	Mechanical:	
Diff. Gain:	<.8%	Size:	5"W x 7.5"D x 1.7" H
Diff. Phase:	<.8°	Weight:	3lbs
H Tilt:	<1%		
V Tilt:	<1%		

**All Specifications Subject To Change Without Prior Notification**

