

# CS-28

# Sequential, RS-232 Video Switcher



## FEATURES:

- High quality Video Performance
- High quality Construction
- UL listed power supply
  - 5 Year Warranty
  - Made in USA

The **CS-28** switcher is an RS-232 controlled, 8 video input with 2 video output vertical interval switcher. Front panel controls are for local monitoring on video out #1 while video out #2 is fed to the remote computer access system.

## SPECIFICATIONS

Video:		Operational:	
Inputs (8):	Composite Video	Switches (8):	3 Position Toggle Switch
Input Connectors:	BNC	Indicators (8):	LED Lamp For Each Input
Input Level:	1.0VPP Nominal, 2VPP Max	BAUD Rate:	9600 BAUD, Preset
Input Impedance:	75ohm +/-5%	RS-232 Connections (2):	2.5mm RCA Jack
Outputs (2):	Composite Video	Control Commands:	Predefined ASCII Codes
Output Connectors:	BNC		For Unit ID And Input Select
Output Impedance:	75ohm +/-5%	<b>Power Requirements:</b>	
Gain In/Out:	Unity Into 75ohms +/- 10%	Power Connector:	3.5mm Phono Plug, Center +
Frequency Response:	0-5MHz +/- .5dB	AC Operation:	Use 12VDC AC Adapter
	5-15MHz + 1.0dB	DC Power Input:	12 To 20 VDC Ungrounded
Diff. Gain:	<.8%	DC Power Draw:	<2.5VA
Diff. Phase:	<.8°	<b>Mechanical:</b>	
H Tilt:	<1%	Size:	8.7"W x 8"D x 1.7"H
V Tilt:	<1%	Weight:	3lbs

**All Specifications Subject To Change Without Prior Notification**

