

CTS-2

Sequential Video Switcher

Compu-Video Systems

CVS



FEATURES:

- High Quality Video Performance
- Alarming: CATS-2
- High Quality Construction
- Terminating: CTS-2
- UL Listed Power Supply
- Made in the USA

The **CTS-2** is a high performance 2x1 composite video sequential switcher. The switcher is designed to handle up to two high resolution color video sources and uses an external UL listed power supply to meet today's safety requirements.

SPECIFICATIONS

Video:		Power Requirements:	
Input Impedance:	75 ohms Terminated	Power:	UL Listed 12VDC Power
Output Impedance:	75 ohms		Adapter (Supplied)
Max Video Input:	2vpp	Input Voltage:	13.5 To 18VDC Isolated
Frequency Response:	15mHz +/- 0.7dB		Ground
Gain:	Unity +/-3%	Power Consumption:	1 Watt
Differential Gain:	<0.5%	Mechanical:	
Differential Phase Error:	<0.5 Degrees	Connectors:	BNC
Max H Tilt:	<1%	Power Connector:	3.5mm Phono, Center +
Max V Tilt:	<1%	Height:	1.30"
Operational		Width:	4.50"
Switches (1):	3 Position Toggle Switch	Depth:	4.50"
Indicators (2):	LED Lamp For Each Input		
Sequence Interval:	Variable 1 sec. To 90 sec.		

All Specifications Subject To Change Without Prior Notification