

# DA-2120

## Multiple Input Video Distribution Amplifier



### FEATURES:

- Two 1x12 Distribution amps in each unit
- High quality Color video performance
- Industrial grade specifications
  - Compact size
- UL listed Power Supply
- Made in the USA

The DA-2120 has 2 high performance 1x12 Color Video distribution Amplifiers in one chassis. Instead of installing 2 separate DA's, use the DA-2120 to save space and money. For less than 1x12 operation use only the outputs needed and simply leave the unused ones unterminated. A UL listed power supply is included with the DA-2120.

## SPECIFICATIONS

<b>Video:</b>		V Tilt:	<1%
Inputs (2):	Composite Video	Crosstalk Between	
Input Connectors:	BNC	Channels (All Hostile):	>60dB @ 3.58MHz
Input Level:	1.0VPP Into 75 ohms	<b>Power Requirements:</b>	
Input Impedance:	75ohm +/-5%	AC Operation:	Use CVT-1250 Adapter
Outputs (24):	12 Per Input		Supplied With Unit
Output Connectors:	BNC	AC Power:	120VAC +10% / -15% / 60Hz
Output Impedance:	75ohm +/-5%	AC Power Draw:	<2w
Gain In/Out:	Unity +/- 3dB Variable	Power Connector:	3.5mm Phono Plug
Frequency Response:	0-15mHz +/- .5dB	<b>Mechanical:</b>	
Power / Supply Hum:	<63dB	Size:	19.00"W x 7.0"D x 1.70"H
H Tilt:	<1%	Weight:	2.5lbs
		Operating Temp Range:	0-40°C With Provided Power Supply
			-35-80°C Without Provided Power
			Supply

**All Specifications Subject To Change Without Prior Notification**

