

DA-3080

Multiple Input Video Distribution Amplifier



FEATURES:

- Eight 1x3 Distribution amps in each unit
- High quality Color video performance
- Industrial grade specifications
 - Compact size
- UL listed Power Supply
 - Made in the USA

The DA-3080 has 8 high performance 1x3 Color Video distribution Amplifiers in one chassis. Instead of installing 8 separate DA's, use the DA-3080 to save space and money. For less than 1x3 operation use only the outputs needed and simply leave the unused ones unterminated. A UL listed power supply is included with the DA-3080.

SPECIFICATIONS

Video:		H Tilt:	<1%
Inputs (8):	Composite Video	V Tilt:	<1%
Input Connectors:	BNC	Crosstalk Between:	
Input Level:	1.0VPP Into 75 ohms	Channels (All Hostile):	>60dB @ 3.58mHz
Input Impedance:	75ohm +/-5%	Power Requirements:	
Outputs (24):	3 Per Input	AC Operation:	Use CVT-1250 Adapter
Output Connectors:	BNC		Supplied With Unit
Output Impedance:	75ohm +/-5%	AC Power:	120VAC +10% / -15% / 60Hz
Gain In/Out:	Unity +/- 3dB Variable	AC Power Draw:	<2w
Diff Gain:	<1%	Power Connector:	3.5mm Phono Plug
Diff. Phase:	<1°	Mechanical:	
Frequency Response:	0-15mHz +/- .5dB	Size:	19.00"W x 7.0"D x 1.70"H
Power / Supply Hum:	<63dB	Weight:	2.5lbs
		Operating Temp Range:	0-40°C With Provided Power Supply
			-35-80°C Without Provided Power
			Supply

All Specifications Subject To Change Without Prior Notification

