

DA-4060

Multiple Input Video Distribution Amplifier, Coax

Compu-Video Systems

CVS



FEATURES:

- Four 1x6 Distribution amps in each unit
- Industrial grade specifications
- UL listed Power Supply
- High quality Color video performance
- Compact size
- Made in the USA

The **DA-4060** has 4 high performance 1x6 Color Video distribution Amplifiers in one chassis. Instead of installing 4 separate DA's, use the **DA-4060** to save space and money. For less than 1x6 operation use only the outputs needed and simply leave the unused ones unterminated. A UL listed power supply is included with the **DA-4060**.

SPECIFICATIONS

| | | | |
|---------------------|------------------------|----------------------------|--|
| Video: | | H Tilt: | <1% |
| Inputs (4): | Composite Video | V Tilt: | <1% |
| Input Connectors: | BNC | Crosstalk Between | |
| Input Level: | 1.0VPP Into 75 ohms | Channels (All Hostile): | >60dB @ 3.58MHz |
| Input Impedance: | 75ohm +/-5% | Power Requirements: | |
| Outputs (24): | 6 Per Input | AC Operation: | Use CVT-1250 Adapter |
| Output Connectors: | BNC | | Supplied With Unit |
| Output Impedance: | 75ohm +/-5% | AC Power: | 120VAC +10% / -15% / 60Hz |
| Gain In/Out: | Unity +/- 3dB Variable | AC Power Draw: | <2w |
| Diff Gain: | <1% | Power Connector: | 3.5mm Phono Plug |
| Diff. Phase: | <1° | Mechanical: | |
| Frequency Response: | 0-15mHz +/- .5dB | Size: | 19.0"W x 6.8"D x 3.50"H |
| Power / Supply Hum: | <63dB | Weight: | 2.5lbs |
| | | Operating Temp Range: | 0-40°C With Provided Power Supply |
| | | | -35-80°C Without Provided Power Supply |

All Specifications Subject To Change Without Prior Notification