

VDA-412

(4) 1x2 Multiple Input
Video Distribution Amplifier, Coax



FEATURES:

- Four 1x2 Distribution amps in each unit
- High quality Color video performance
- Industrial grade specifications
- Compact size
- UL listed Power Supply
- Made in the USA

The **VDA-412** has four high performance, 1x2 Color Video distribution Amplifiers in one chassis. Instead of installing 4 separate DA's, use the **VDA-412** to save space and money. For 1x1 operation use only the outputs needed and simply leave the unused one unterminated. A UL listed power supply is included with the **VDA-412**.

SPECIFICATIONS			
Video:		H Tilt:	<1%
Inputs (4):	Composite Video, NTSC or PAL	V Tilt:	<1%
Input Connectors:	BNC	Crosstalk Between CH:	>60dB @ 3.58mHz
Input Level:	1.0VPP Into 75 ohms	Power Requirements:	
Input Impedance:	75ohm +/-5%	AC Operation:	Use CVT-1250 Adapter
Outputs (8):	2 Per Input		Supplied With Unit
Output Connectors:	BNC	AC Power:	120VAC +10% / -15% / 60Hz
Output Impedance:	75ohm +/-5%	AC Power Draw:	<1w
Gain In/Out:	Unity	Power Connector:	3.5mm Phono Plug
Diff Gain:	<1%	Mechanical:	
Diff. Phase:	<1°	Size:	8.00"W x 8.5"D x 1.65"H
Frequency Response:	0-60mHz +/- .5dB	Weight:	1.5lbs
Power / Supply Hum:	<63dB	Operating Temp Range:	0-40°C With Provided Power Supply
			-35-80°C Without Provided Power
			Supply

All Specifications Subject To Change Without Prior Notification